

# SXP

## SERIES

Speed  
up to 80/min

Capable of  
overwrapping  
and banding

Processes  
paper and  
(bio)film



DISCOVER MORE





# SXP series

100% servo overwrapper.  
Limited investment.



Reliable



High quality




Eco friendly



Excellent results



Flexible



## > Benefits

- ▶ High quality and reliable production machine
- ▶ Full-servo
- ▶ Standard OMAC PackML
- ▶ Vacuum film infeed
- ▶ Individual product transfer (IPT)
- ▶ Touch screen
- ▶ Excellent product presentation and protection
- ▶ Tight and attractive wrapping
- ▶ Reduction of production costs
- ▶ Processes recyclable BOPP and paper<sup>1</sup>
- ▶ Easy accessible machine
- ▶ Flexible size range
- ▶ Various infeed directions

<sup>1</sup>Uncommon heat-sealable wrapping materials are subject to testing and evaluation.

## > Technical details

Max output <sup>2</sup>	<b>80 /min</b>
Min product size (mm) <sup>3</sup>	<b>L 40 W 40 (20) H 25 (7)</b>
Max product size (mm) <sup>3</sup>	<b>L 300 W 225 H 96 (125)</b>
Film width range	<b>50 - 435 mm</b>
Max film roll diameter	<b>400 mm</b>

<sup>2</sup>Depending on product and packaging material.

<sup>3</sup>Figures between brackets represent optional modifications.