

# SX

## SERIES

Speed  
up to 80/min

Capable of  
overwrapping  
and banding

Processes  
paper and  
(bio)film



DISCOVER MORE





# SX series

Efficiency and flexibility  
combined in one overwrapper.



Reliable



High quality




Eco friendly



Excellent results



Flexible



## ► Benefits

- High quality and reliable production machine
- Touch screen
- Individual product transfer
- Vacuum film feed
- Servo machine pusher
- Optional collating devices
- Excellent product presentation and protection
- Tight and attractive wrapping
- Reduction of production costs
- Processes recyclable BOPP and paper<sup>1</sup>
- Easy accessible machine
- Fast and easy product change over
- Flexible size range
- Various infeed directions

<sup>1</sup>Uncommon heat-sealable wrapping materials are subject to testing and evaluation.

## ► Technical details

Max output <sup>2</sup>	<b>80 /min</b>
Min product size (mm) <sup>3</sup>	<b>L 40 W 40 (20) H 16 (7)</b>
Max product size (mm) <sup>3</sup>	<b>L 300 (360) W 225 (265) H 96 (125)</b>
Film width range	<b>50 - 435 mm</b>
Max film roll diameter	<b>400 mm</b>

<sup>2</sup>Depending on product and packaging material.

<sup>3</sup>Figures between brackets represent optional modifications.